

QSC TANK, INC.

ISO Tank Containers

ISO TYPE	SIZE	CAPACITY	WORKING PRESSURE	CONSTRUCTION MATERIAL	LOADING MEDIUM
T3	20 ft	22.50 m ³	0.175 MPa	Q345R	Bitumen
T4	20 ft	19~26 m ³	0.18 MPa	304	Food Grade Liquids, Oils, Petro Chemicals
T11	20 ft	16~26 m ³	0.40 MPa	316L	Non-Hazardous Liquid Chemicals
T14 Rubber Lining	20 ft	16~21 m ³	0.40 MPa	304 Q345 R	Corrosive Liquid Chemicals (Hydrochloric Acid)
T14 HDPE Lining	20 ft	19~21 m ³	0.40 MPa	SA516M	Corrosive Liquid Chemicals (Ferric Chloride Solution, Sodium Hypochlorite, Hydrofluoric Acid)
T20	20 ft	14.50~21 m ³	0.67 MPa	316L SA516M	Anhydrous Hydrofluoric Acid, Titanium, Tetrachloride
T50	20 ft	24.50 m ³	2.2 MPa	Q345R	LPG, Propane, Butane, Butylene, Trimethylene, Dimethylamine, Dimethylether, Isobutene, Chlorine
T50	20 ft	24 m ³	1.38 MPa	SA612M	LPG, Propane, Butane, Butylene, Trimethylene, Dimethylamine, Dimethylether, Isobutene, Chlorine
T50	20 ft	22 m ³	2.75 MPa	SA612M	LPG, Propane, Butane, Butylene, Trimethylene, Dimethylamine, Dimethylether, Isobutene, Chlorine
T50	20 ft	24.30 m ³	3.44 MPa	P460NL1	LPG, Propane, Butane, Butylene, Trimethylene, Dimethylamine, Dimethylether, Isobutene, Chlorine
T50	40 ft	50 m ³	1.80 MPa	Q345R	LPG, Propane, Butane, Butylene, Trimethylene, Dimethylamine, Dimethylether, Isobutene, Chlorine
T75	20 ft	19.80 m ³	1.60 MPa	Inner Shell 304 Outer Shell SA516M Gr 485	LNG, LN ₂ , LO ₂ , LAr, LN ₂ O, LC ₂ H ₆
T75	20 ft	20.8 m ³	2.40 MPa	Inner Shell 15Mn DR Outer Jacket Q345R	CO ₂
T75	40 ft	45.58 m ³	0.75 MPa	Inner Shell SA240M Outer Jacket SA516M Gr 485	LNG, LN ₂ , LO ₂ , LAr, LN ₂ O, LC ₂ H ₆